

MOUNTED AMENDMENT SPREADERS #R 1500 - R 2000 - R 2500 - R 3000

Strong points

1. Unique decompaction process , the 2 augers are driven in opposite directions to decompress the product thus avoiding the arch effect. The product feeds the distribution ramps evenly.
2. Tractor PTO drives the augers directly to eliminate maintenance requirements.
3. Connecting the 2 auger motors in series ensures the same rotation speed on the 2 motors for similar distribution at the booms.
4. The bottom, hopper augers and opening grille are made of stainless steel to ensure maximum tool life and prevent rust to obtain a tool that lasts over time.



Focus



7 m spread boom
For a larger area covered in a single pass.



Stainless steel bottom and screw
Prevents rust and premature wear of the bottom of the body and the augers to obtain a tool that lasts over time.



Electrical Control
Control of all machine functions from the tractor cab; it can be used to adjust the rate per hectare.

MOUNTED AMENDMENT SPREADERS

Model	R 1500	R 2000	R 2500	R 3000
Capacity [L]	1500	2000	2500	3000
Overall width [cm]	250			
Hopper width [cm]	248			
Spreading width [cm]	600			
Loading height [cm]	1,21	1,28	1,47	1,7
Hydraulic function	1 single acting return + 1 DE			
Empty weight	570	600	620	700